



New Construction Window

2900 Single Hung and 2950/2960 Fixed Window Series

Structural and Thermal Performance Ratings

Structural Test Information					
<i>Silverline Windows are tested and certified to the AAMA/NWDA 101/I.S.2 specification for structural performance.</i>					
Window Series	Window Size	Air Infiltration @ 25 MPH	Water Resistance	Structural Test Pressure	DP Rating
2900 Single Hung	36" x 62"	0.13 CFM	7.50 PSF	75.0 PSF	DP-50
	38" x 60"	0.13 CFM	7.50 PSF	75.0 PSF	DP-50
	44" x 62"	0.13 CFM	7.50 PSF	67.5 PSF	DP-45
	107" x 48"	0.22 CFM	7.50 PSF	52.0 PSF	DP-35
	107" x 62"	0.22 CFM	7.50 PSF	75.0 PSF	DP-50
2950/2960 Fixed Lite	87" x 62"	0.08 CFM	7.50 PSF	60.0 PSF	DP-40

Thermal Test Information					
<i>Silverline Windows are tested and certified to the NFRC 100-97 specification for the thermal performance of the entire window unit.</i>					
Window Series	Glazing Type	U Value	SHGC	Visible Light Transmittance	Energy Star Compliance
2900 Single Hung	LoE ² I.G.	0.35	0.34	0.58	All Regions
	LoE ² I.G. W/ Flat Grille	0.35	0.30	0.52	All Regions
2950/2960 Fixed Lite	LoE ² I.G.	0.35	0.34	0.59	All Regions
	LoE ² I.G. W/ Flat Grille	0.35	0.31	0.52	All Regions